Product data sheet
Characteristics

LVS03342
TRANSPARENT FRONT PLATE W600/W650 4M



Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT G enclosure PrismaSeT P cubicle PrismaSeT Pack 160 enclosure
Type of front plate	Transparent
Installed device	TeSys: fixed TeSys U - horizontal installation TeSys: fixed GV2 + D or K contactors <= 40 A - horizontal installation PowerLogic: iEM3000 PowerLogic: PM3000
Poles description	9 x 3P: modular rail support: TeSys U horizontal installation 9 x 3P: modular rail support: GV2 + D or K contactors <= 40 A horizontal installation
Operating position	Horizontal

Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm Pack enclosure - width 555 mm
Connection position	Direct connection
Number of vertical modules [50 mm]	4
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA
Material	Glass
Surface finish	Textured Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	200 mm
Width	500 mm
Net weight	0.98 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Quantity per set	Set of 1
Functional unit	600 mm PrismaSeT G floor-standing enclosure TeSys GV2 + D or K contactors <= 40 A fixed horizontal 3P 9 direct 5 600 mm PrismaSeT G wall-mounted enclosure TeSys GV2 + D or K contactors <= 40 A fixed horizontal 3P 9 direct 5 650 mm 400 mm PrismaSeT P cubicle TeSys GV2 + D or K contactors <= 40 A fixed horizontal 3P 9 direct 5 650 mm 400 mm PrismaSeT P cubicle PowerLogic 3 4 650 mm 400 mm PrismaSeT P cubicle PowerLogic 4 4 600 mm PrismaSeT G floor-standing enclosure TeSys TeSys U fixed horizontal 3P 9 direct 5 600 mm PrismaSeT G wall-mounted enclosure TeSys TeSys U fixed horizontal 3P 9 direct 5 600 mm PrismaSeT G floor-standing enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4 600 mm PrismaSeT G wall-mounted enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4 650 mm 400 mm PrismaSeT P cubicle TeSys TeSys U fixed horizontal 3P 9 direct 4 555 mm Pack 160 Pack enclosure TeSys GV2 + D or K contactors <= 40 A fixed horizontal 3P 9 direct 5 555 mm Pack 160 Pack enclosure TeSys TeSys U fixed horizontal 3P 9 direct 5 555 mm Pack 160 Pack enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.058 kg
Package 1 Height	3 cm
Package 1 width	21.5 cm
Package 1 Length	51.5 cm
Unit Type of Package 2	P12
Number of Units in Package 2	64
Package 2 Weight	81.0 kg
Package 2 Height	36 cm
Package 2 width	80 cm
Package 2 Length	120 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	8
Package 3 Weight	8.672 kg
Package 3 Height	16 cm
Package 3 width	23 cm
Package 3 Length	53 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product