

Product data sheet

Characteristics

LVS04018

LINERGY FM 4P DIS.BLOCK 160A 12M

27HOLES



Main

Range	Linergy
Range of product	Linergy
Product or component type	Device feeder
Product name	Linergy FM
Range compatibility	PrismaSeT G enclosure PrismaSeT P enclosure Prisma PH enclosure PrismaSeT Pack 160 enclosure PrismaSeT Pack 250 enclosure
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Mounting support	Slotted backplate DIN rail Plain backplate
Installed device	Modular device
Poles description	3P + N
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	160 A
[In] rated current	160 A at 40 °C
[Ipk] rated peak withstand current	20 kA
I²t on activation	6700000 A².s
Connections - terminals	Supply: crimped lug50 mm² Supply: flexible bars, 20 x 3 mm Distribution: quick-connect terminal strips (phase) , 6 x 4...10 mm² (flexible) Distribution: quick-connect terminal strips (phase) , 6 x 4...10 mm² (rigid) Distribution: quick-connect terminal strips (neutral) , 6 x 4...10 mm² (flexible) Distribution: quick-connect terminal strips (neutral) , 6 x 4...10 mm² (rigid)
9 mm pitches	24
Total number of 18 mm modules	12
Net weight	0.92 kg
Colour	Anthracite grey (RAL 7016)

Environment

Standards	IEC 61439-1, inside enclosure IEC 61439-2, inside enclosure IEC 60947-7-1
Product certifications	ASTA

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	943.0 g
Package 1 Height	6.8 cm
Package 1 width	7.8 cm
Package 1 Length	24.2 cm
Unit Type of Package 2	P06
Number of Units in Package 2	110
Package 2 Weight	110.0 kg
Package 2 Height	59 cm
Package 2 width	60 cm
Package 2 Length	80 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	4.729 kg
Package 3 Height	7 cm
Package 3 width	24.2 cm
Package 3 Length	38.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product