Product data sheet
Characteristics

LVS04041
Distribution block, Linergy DX, 4P, 63A, 4 modules, 24 holes, quick connect bottom

Main

Range	Linergy
Product or component type	Distribution block
Product name	Linergy DX
Range compatibility	Prisma PrismaSeT Pragma
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Location of connection	Bottom
Mounting support	DIN rail
Poles description	4P
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	63 A at 40 °C
[In] rated current	63 A at 40 °C
Connections - terminals	Supply: tunnel type terminal16 mm² (flexible) Supply: tunnel type terminal25 mm² (rigid) Distribution: spring terminal (phase) , 12 x 2.5…6 mm² (flexible) Distribution: spring terminal (phase) , 12 x 2.5…6 mm² (rigid) Distribution: spring terminal (neutral) , 12 x 2.5…6 mm² (flexible) Distribution: spring terminal (neutral) , 12 x 2.5…6 mm² (rigid)
9 mm pitches	8
Total number of 18 mm modules	4
Net weight	0.29 kg

Environment

Pollution degree	3
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 60947-7-1 IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	316.0 g
Package 1 Height	7.6 cm
Package 1 width	8 cm
Package 1 Length	10.4 cm
Unit Type of Package 2	S03

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Number of Units in Package 2	30
Package 2 Weight	9.921 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Life Is On Schneider Electric