# Product data sheet
## Characteristics

# LVS08083
## PLAIN DOOR 3R PACK 160



### Main

| | |
|---|---|
| Range | PrismaSeT |
| Range of product | PrismaSeT G |
| Product or component type | Door |
| Product name | Pack 160 |
| Range compatibility | PrismaSeT G enclosure |
| Provided equipment | Door<br>Handle<br>Keylock (key 405)<br>Other keylock and insert to be ordered separately<br>2 hinge |
| Enclosure mounting | Flush with kit<br>Surface |
| Type of door | Plain |
| IP degree of protection | IP30 |

### Complementary

| | |
|---|---|
| Installation description | Pack enclosure - width 555 mm<br>Extension enclosure - width 555 mm |
| Door opening side | Reversible |
| Number of locks | 1 |
| Door opening angle | 130 ° |
| Number of 18 mm modules per row | 24 |
| Total number of 18 mm modules | 72 |
| Number of vertical modules [50 mm] | 12 |
| Number of horizontal rows | 3 |
| Enclosure material | Treated sheet steel |
| Quantity per set | Set of 1 |
| Height | 630 mm |
| Width | 550 mm |
| Depth | 22 mm |
| Net weight | 3.8 kg |
| Surface finish | Matt<br>Textured |
| Colour | White (RAL 9003) |

### Environment

| | |
|---|---|
| IK degree of protection | IK08 conforming to EN/IEC 62262 |
| Standards | IEC 61439-2<br>IEC 61439-1 |
| Protective treatment | Electrophoresis treatment and hot-polymerised polyester epoxy powder |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 4.405 kg |
| Package 1 Height | 6 cm |
| Package 1 width | 61 cm |
| Package 1 Length | 67.5 cm |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 30 |
| Package 2 Weight | 144.0 kg |
| Package 2 Height | 98 cm |
| Package 2 width | 80 cm |
| Package 2 Length | 120 cm |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |