Product data sheet
Characteristics

R9D08610
Residual current breaker with overcurrent protection (RCBO), Resi9, 1P+N, 10A, C curve, 6000A, A type, 30mA, 36mm wide



Main

Range	Resi9
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Poles description	1P + N
Number of protected poles	1
[In] rated current	10 A at 30 °C conforming to AS/NZS 61009.1
Network type	AC
Curve code	C
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A
Breaking capacity	6000 A Icn at 230 V AC 50/60 Hz
Quality labels	RCM

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	230 V AC 50/60 Hz
Limitation class	3
[Ui] rated insulation voltage	440 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 kV
Comb busbar and distribution block compatibility	YES
9 mm pitches	4
Height	91 mm
Width	36 mm
Depth	75 mm
Net weight	268 g
Grid distance	45 mm
Connections - terminals	Tunnel type terminal - 1...16 mm² - rigid Tunnel type terminal - 1...10 mm² - flexible
Temperature derating table	-25 °C (12.1 A) -20 °C (12.1 A) -15 °C (11.8 A) -10 °C (11.6 A) -5 °C (11.4 A) 0 °C (11.2 A) 5 °C (11.02 A) 10 °C (10.8 A) 15 °C (10.6 A) 20 °C (10.4 A) 25 °C (10.2 A) 30 °C (10 A) 35 °C (9.8 A) 40 °C (9.6 A) 45 °C (9.3 A) 50 °C (9.1 A) 55 °C (8.9 A) 60 °C (8.6 A) 65 °C (8.4 A) 70 °C (8.1 A)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	IEC 61009-2-2 EN/IEC 61009-1 AS/NZS 61009.1
IP degree of protection	IP20
Pollution degree	2
Overvoltage category	III
Ambient air temperature for operation	-25…70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	3.6 cm
Package 1 Length	9.08 cm
Package 1 Weight	0.21 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	40
Package 2 Height	20 cm
Package 2 Width	29.9 cm
Package 2 Length	39.8 cm
Package 2 Weight	8.4 kg
Unit Type of Package 3	P06
Number of Units in Package 3	480
Package 3 Height	75 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	106.8 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Under investigation