Product data sheet
Characteristics

R9HSB110F
Switchboard enclosure, Resi9, type 2, 1 row, 10 ways, Flush mounted

Main

Range	Resi9
Product or component type	Enclosure
Device application	Distribution
Number of 18 mm modules per row	15

Complementary

Enclosure mounting	Flush
[Ue] rated operational voltage	230/400 V AC
[In] rated current	100 A
[Ui] rated insulation voltage	500 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.8 cm
Package 1 Width	25.6 cm
Package 1 Length	28.4 cm
Package 1 Weight	1.94 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.