

Product data sheet

Characteristics

SAU40024273DF

SAU Chassis, Acti9, 400A, 3Ph, 24 poles,
27mm for C120 MCB, dual feed



Main

Range	Acti9
Product or component type	Chassis
Device application	Distribution

Complementary

Incomer device	Switch disconnecter - 3P MCCB - 3P
Protection device type	Miniature circuit breaker (MCB) as outgoer
Network type	AC
[In] rated current	400 A
Number of ways	1 way (incomer) - 3P 1 way (outgoer) - 1P or 3P
Rated voltage	415 V 50 Hz
Short-circuit withstand	25 kA 0.1 s
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Number of poles	24
Number of poles	24 x 27 mm
Width	245 mm
Length	610 mm
Depth	95 mm
Net weight	3.6 kg
Busbar pitch	27 mm
Location of connection	Dual feed

Environment

Standards	AS/NZS 61439
-----------	--------------

Packing Units

Unit Type of Package 1	PCE
Package 1 Length	61 cm
Number of Units in Package 1	1
Package 1 Width	24.5 cm
Package 1 Height	9.5 cm
Package 1 Weight	3.3 kg

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope