Product data sheet
Characteristics

SAU40036273
SAU Chassis, Acti9, 400A, 3Ph, 36 poles, 27mm for C120 MCB, top or bottom feed



Main

Range	Acti9
Product or component type	Chassis
Device application	Distribution

Complementary

Incomer device	Switch disconnector - 3P MCCB - 3P
Protection device type	Miniature circuit breaker (MCB) as outgoer
Network type	AC
[In] rated current	400 A
Number of ways	1 way (incomer) - 3P 1 way (outgoer) - 1P or 3P
Rated voltage	415 V 50 Hz
Short-circuit withstand	25 kA 0.1 s
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Number of poles	36
Number of poles	36 x 27 mm
Width	245 mm
Length	680 mm
Depth	95 mm
Net weight	4.56 kg
Busbar pitch	27 mm
Location of connection	Top or bottom

Environment

Standards	AS/NZS 61439

Packing Units

Unit Type of Package 1	PCE
Package 1 Length	25 cm
Number of Units in Package 1	1
Package 1 Width	67 cm
Package 1 Height	9.5 cm
Package 1 Weight	3.89 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope