

## Product data sheet

### Characteristics

# SAU40042273DF

SAU Chassis, Acti9, 400A, 3Ph, 42 poles,  
27mm for C120 MCB, dual feed



### Main

|                           |              |
|---------------------------|--------------|
| Range                     | Acti9        |
| Product or component type | Chassis      |
| Device application        | Distribution |

### Complementary

|                                        |                                                    |
|----------------------------------------|----------------------------------------------------|
| Incomer device                         | Switch disconnecter - 3P<br>MCCB - 3P              |
| Protection device type                 | Miniature circuit breaker (MCB) as outgoer         |
| Network type                           | AC                                                 |
| [In] rated current                     | 400 A                                              |
| Number of ways                         | 1 way (incomer) - 3P<br>1 way (outgoer) - 1P or 3P |
| Rated voltage                          | 415 V 50 Hz                                        |
| Short-circuit withstand                | 25 kA 0.1 s                                        |
| [Ui] rated insulation voltage          | 500 V                                              |
| [Uimp] rated impulse withstand voltage | 6 kV                                               |
| Number of poles                        | 42                                                 |
| Number of poles                        | 42 x 27 mm                                         |
| Width                                  | 245 mm                                             |
| Length                                 | 853 mm                                             |
| Depth                                  | 95 mm                                              |
| Net weight                             | 5.76 kg                                            |
| Busbar pitch                           | 27 mm                                              |
| Location of connection                 | Dual feed                                          |

### Environment

|           |              |
|-----------|--------------|
| Standards | AS/NZS 61439 |
|-----------|--------------|

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Package 1 Length             | 85.3 cm |
| Number of Units in Package 1 | 1       |
| Package 1 Width              | 24.5 cm |
| Package 1 Height             | 9.5 cm  |
| Package 1 Weight             | 5.1 kg  |

Offer Sustainability

|                   |                                                                                                                     |
|-------------------|---------------------------------------------------------------------------------------------------------------------|
| REACH Regulation  |  <a href="#">REACH Declaration</a> |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope                                                                          |