

Product data sheet

Characteristics

A9A15212

Acti9 modular bell transformer iTR - 230 V
50..60 Hz - output 8..12 V - 16 VA



Main

Range of product	Acti 9
Product name	Acti 9 iTR
Product or component type	Transformer
Device short name	ITR
Transformer type	Bell transformer

Complementary

[Ue] rated operational voltage	230 V AC 50/60 Hz
Output voltage	8/12 V: +/- 15 % on load 13/18 V: off load
Output short-circuit protection	Built-in
Rated power in VA	16 VA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	4
Height	89 mm
Width	36 mm
Depth	60 mm
Colour	White
Auxiliary connection terminal	Tunnel type terminalsrigid 2.5 mm ² Tunnel type terminalsflexible 2.5 mm ² Tunnel type terminalsflexible with ferrule 2.5 mm ²
Wire stripping length	6 mm
Tightening torque	0.5 N.m

Environment

Standards	IEC 61558-2-6 EN 61558-2-6 EN 60742
Product certifications	NF
IP degree of protection	IP20 conforming to IEC 60529
Overvoltage category	Class II with terminal shields in option
Ambient air temperature for operation	-20...55 °C
Ambient air temperature for storage	-25...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	374 g
Package 1 Height	4 cm
Package 1 width	7.5 cm
Package 1 Length	9.5 cm
Unit Type of Package 2	S02
Number of Units in Package 2	28
Package 2 Weight	10.838 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	400
Package 3 Weight	166.504 kg
Package 3 Height	50 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------