

Product data sheet

Characteristics

ACTRJSMTG6ANSSP

Actassi - modular jack - category 6A - 10G -
FTP - non shuttered - panel version



Main

Range	Actassi
Product brand	Schneider Electric
Product type	Keystone modular jack
Product specific application	For panel
Provided equipment	Without shutter
Colour tint	Metal (zamak)
Wiring Colour configuration	TIA-568A/B
Type of packing	Plastic bag and carton
Quantity per set	Set of 1

Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Insulation resistance	>= 500 MOhm
Connector type	RJ45
Tool type	Punch down tool Quick termination tool
Cable outer diameter	0.9...1.4 mm
Compatible LAN cable types	STP
Communication network category	6A
Supported applications	10GBASE-T
Product compatibility	RJ45 plug
Type of footprint	S-110 keystone
Targeted region	Asia Pacific.

Environment

Operational temperature range	-10...60 °C
Ambient air temperature for storage	-20...70 °C
Relative humidity	0...93 %
Climatic category	40/070/21 (21 days)
Flame retardance	UL94-V0 conforming to UL listed
Product certifications	FCC part 68 F IEC 60603-7
Standards	ISO/IEC 11081 IEC 60603-7 ANSI/TIA/EIA-568-B

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	30 g
Package 1 Height	1.533 cm
Package 1 width	2.313 cm
Package 1 Length	3.984 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------