

Product data sheet

Characteristics

TPSAUX33

auxiliary contact, TransferPacT, indication for OFF position



Main

Range of product	TransferPacT
Product or component type	Auxiliary Contact Module
Device application	Signalling

Complementary

Auxiliary contact composition	2 NO + 2 NC
Signalling function	Switch position (off)
Auxiliary connection terminal	Screw clamp terminal
Mounting mode	Clip-on
Mounting position	Right-angled
Tightening torque	0.6 N.m +/- 0.1 N.m
Height	90 mm
Width	17.5 mm
Depth	49.5 mm
Net weight	60 g
Accessory / separate part category	Signalling accessory

Environment

IP degree of protection	IP20
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.3 cm
Package 1 Width	5.8 cm
Package 1 Length	12.0 cm
Package 1 Weight	180.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information