

Product data sheet

Specifications



Actassi S-One Connector RJ45 Shielded Cat 6A DPM box x 12

VDIB1771XB12

Main

Range	Actassi
Product type	RJ45 network socket
Device presentation	Integrated one piece design
Colour tint	Connector: silver (zamak) Wire organizer: dark blue (ABS + PC)
Wiring Colour configuration	568 A/B
Type of packing	Carton
Quantity per set	Set of 12

Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts 1500 V AC/DC peak, between contacts and shield
Contact resistance	20 mOhm
Insulation resistance	Initial insulation resistance: >= 500 MOhm at 100 V DC
AWG gauge	AWG 24...AWG 23
Durability	750 cycles
Coupling attenuation	>= 45 dB at 30...100 MHz >= 85 - 20 x log(f) dB at 100...1000 MHz
Contact pins	8 pins of copper alloy and gold plated conforming to IEC 60603-7
Shield Type	Metallic: 360° self adjusting + drain wire contact Integrated short circuit barrier
Pulling force	50 N during 60 s
Transfer impedance	<= 0.1 Ohm at 1 MHz <= 0.2 Ohm at 10 MHz <= 1.6 Ohm at 80 MHz
Transverse conversion loss	>= 50 dB >= 68 - 20 x log(f) dB at 1...500000 kHz
Tool type	Without tool
Cable outer diameter	0.9...1.4 mm
Compatible LAN cable types	STP
Communication network category	6A

Supported applications	10GBASE-T
Protocols	VoIP (Voice IP) PoE+ (Power over Ethernet) 4PPoE 100W (Power over Ethernet)
Product compatibility	RJ45 plug
Transmission frequency	0...500 MHz
Type of footprint	S-One DPM
Height	28 mm
Length	35 mm
Width	18 mm
Targeted region	Europe Asia Pacific.

Environment

Operational temperature range	-40...70 °C
Climatic category	40/070/21 (21 days)
Flame retardance	UL94-V0
Standards	ANSI/TIA-568-C.2 IEC 60603-7-5 ISO/IEC 11801:2011 Ed.2.2 UL 1863

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	30.0 g
Package 1 Height	1.9 cm
Package 1 width	2.9 cm
Package 1 Length	3.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	390.0 g
Package 2 Height	4.4 cm
Package 2 width	8.2 cm
Package 2 Length	18.2 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	216
Package 3 Weight	7.346 kg
Package 3 Height	15.4 cm
Package 3 width	29.4 cm
Package 3 Length	38.6 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration

Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------