

Product data sheet

Characteristics

VDIB17735UWE

Category 5e, UTP 30 Mech, Shutter Modular Jack, White



Main

Range	Actassi
Product brand	Schneider Electric
Product type	30Mech modular jack
Provided equipment	With shutter
Colour tint	White
Wiring Colour configuration	TIA-568A/B
Type of packing	Plastic bag and carton
Quantity per set	Set of 1

Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Insulation resistance	>= 500 MOhm
AWG gauge	AWG 24...AWG 22
Durability	750 cycles
Tool type	Punch down tool Quick termination tool
Cable outer diameter	0.7...1.4 mm
Compatible LAN cable types	UTP
Communication network category	5e
Product compatibility	RJ45 plug
Type of footprint	S-110 30 mech
Targeted region	Asia Pacific.

Environment

Operational temperature range	-10...60 °C
Ambient air temperature for storage	-20...70 °C
Climatic category	40/070/21 (21 days)
Flame retardance	UL94-V0 conforming to UL listed
Product certifications	FCC part 68 F IEC 60603-7
Standards	IEC 11801 class E NZS 3080:2003 class E TIA/EIA 568 B

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.008 kg
Package 1 Height	3 cm
Package 1 width	3 cm

Package 1 Length	2 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	0.256 kg
Package 2 Height	15.5 cm
Package 2 width	12.7 cm
Package 2 Length	18.2 cm
Unit Type of Package 3	S04
Number of Units in Package 3	280
Package 3 Weight	4.836 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------