

Product datasheet

Specifications



Changeover switch, Acti9, 4P, 63A, 400/415VAC

A9SCO463

Main

Range	Acti9
Product name	Acti9 iSSW
Product or component type	Changeover switch
Device short name	iSSW
Device application	Change source of supply
poles description	4P
Contacts type and composition	4 C/O
[Ie] rated operational current	63 A
[Ue] rated operational voltage	400/415 V
network type	AC
network frequency	50/60 Hz
Utilisation category	AC-23A AC-22A

Complementary

[Ui] rated insulation voltage	690 V
[Uimp] rated impulse withstand voltage	6 kV
[Icm] peak rated short-circuit making capacity	1.26 kA
[Icw] rated short-time withstand current	1.26 kA during 1 s at 400/415 V
Rated operational power in W	23.4 kW at 415 V (AC-23A) 22.5 kW at 400 V (AC-23A) 36.2 kW at 415 V (AC-22A) 35 kW at 400 V (AC-22A)
Control type	Toggle 3 positions
mounting support	35 mm DIN rail
mounting position	Vertical Any position
Locking options description	Padlock in ON position
Connections - terminals	Screw terminals (top and bottom) 1...16 mm ² flexible Screw terminals (top and bottom) 1...16 mm ² flexible with ferrule Screw terminals (top and bottom) 1...25 mm ² rigid
Wire stripping length	12 mm for top and bottom connection
Tightening torque	4 N.m top and bottom
Suitability for isolation	Yes

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contact position indicator	Yes
Electrical durability	7000 cycles
Mechanical durability	10000 cycles
9 mm pitches	12
Height	85 mm
Width	105 mm
Depth	44 mm
Net weight	448 g

Environment

Standards	EN/IEC 60947-3 AS/NZS 60947-3
Quality labels	CE RCM
IP degree of protection	IP20 IP40 inside enclosure
Pollution degree	3
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	11.5 cm
Package 1 Length	11 cm
Package 1 Weight	505 g
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	9.5 kg
Unit Type of Package 3	P06
Number of Units in Package 3	216
Package 3 Height	104.6 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	123 kg

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓

Mercury Free

✓

Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations