

Product data sheet

Specifications



SAU Chassis, Acti9, 250A, 3Ph, 108 poles, 18mm for iC60 MCB and RCBO, dual feed

SAU250108183DF

Main

Range	Acti9
Product or component type	Chassis
Device application	Distribution

Complementary

Range compatibility	distribution board
Network type	AC
[In] rated current	250 A
Number of ways	1 way (incomer) - 3P
Rated voltage	415 V 50 Hz
Short-circuit withstand	25 kA 0.1 s
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Number of poles	108
	108 x 18 mm
Width	215 mm
Length	974 mm
Busbar pitch	18 mm
Location of connection	Dual feed

Environment

Standards	AS/NZS 61439
-----------	--------------

Packing Units

Unit Type of Package 1	PCE
Package 1 Length	125.8 cm
Number of Units in Package 1	1
Package 1 Width	24.5 cm
Package 1 Height	9.5 cm

Package 1 Weight	7.9 kg
------------------	--------

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information