


Product data sheet

Characteristics

SAU40012183DF

SAU Chassis, Acti9, 400A, 3Ph, 12 poles,
18mm for iC60 MCB and RCBO, dual feed



Main

Range	Acti 9
Product or component type	Chassis
Device application	Distribution

Complementary

Incomer device	Switch disconnecter - 3P MCCB - 3P
Protection device type	Miniature circuit breaker (MCB) as outgoer Residual current circuit breaker with overcurrent protection (RCBO) as outgoer
Network type	AC
[In] rated current	400 A
Number of ways	1 way (incomer) - 3P 1 way (outgoer) - 1P or 3P
Rated voltage	415 V 50 Hz
Short-circuit withstand	25 kA 0.1 s
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Number of poles	12
Number of poles	12 x 18 mm
Width	245 mm
Length	394 mm
Depth	95 mm
Net weight	1.8 kg
Busbar pitch	18 mm
Location of connection	Dual feed

Environment

Standards	AS/NZS 61439
-----------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.893 kg
Package 1 Height	10.3 cm
Package 1 Width	24.2 cm
Package 1 Length	42.5 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope