


Specifications

POWER	POWER
Power supply AC	110-230V $\pm$ 10%, 50/60Hz
Power supply DC	No
SPECIAL FUNCTIONS	SPECIAL FUNCTIONS
Contactor Control	Yes - max 2A
Roller shutter mode	No
Device temperature protection	Yes
Overload protection	No
Power measurement	Yes
FEATURES	FEATURES
Channels	2 Channel
Operational temperature	0 to + 40 °C
Device power consumption	< 1 W
Intelligent On/Off	Yes
Local and remote control	Yes
Sunrise/Sunset	Yes
Weekly Schedule	Yes
UL Listed option	No
CONNECTIVITY	CONNECTIVITY
Wireless/WiFi Protocol	802.11 b/g/n
Radiofrequency	2400 - 2500 MHz
Range	up to 50m outdoors and up to 30m indoors (Depending on the building materials)
DIMENSIONS	DIMENSIONS
Size	39mm x 36mm x 17 mm



SHELLY-EM-50A	WI-FI ENERGY METER 50A 110-230VAC WITH 50AMP CLAMP CT
SHELLY-EM-120A	WI-FI ENERGY METER 120A 110-230VAC WITH 120AMP CLAMP CT
SHELLY-CLAMP-50	CLAMP CT 50Amp for EM and 3EM Energy Meter
SHELLY-CLAMP-120	CLAMP CT 120Amp for EM and 3EM Energy Meter