SITEMATE SM7.06

32 Amp Temporary Power Distribution Unit

APPLICATIONS:

- Used for temporary power reticulation
- Construction Industry
- Heavy Industry
- Indoor / outdoor events
- Ports



CONSTRUCTION:

- 6 x 15A sockets single phase 3 pin
- Supply - 32A 3ph + N + E 415Va.c IEC 60309
- Frequency 50 - 60Hz
- RCD - 4 Pole, 30mA, 40A 415Va.c
- IP44 / IP65
- Includes 10kA RCD and 15kA MCB as standard
- Specially blended polyethylene enclosure
- Meets AS/NZS 61439.4 requirements for assemblies for construction sites.
- **Dimensions** - 517mm (L) x 280mm (H) x 268mm (W)

PRODUCT FEATURES:

- 2 Year Limited Warranty.
- Stackable for storage and transportation.
- 40mm ground clearance.
- Third party tested.
- Impact resistant robust enclosure for outdoor use.
- Assembled with standard industrial sockets allowing hassle free replacement.
- Customisation available on request.
- Assembled with trade tested components.
- Designed for NZ & AU conditions.

Code	Supply Power	Socket Outlets	Weight
SM7.06	32A, 3 Phase + N + E 415Va.c IEC 60309	6 x 15A single phase 3 pin	8Kgs

Sitemate Power Systems has taken every precaution to ensure accurate information on this data page, but accept no liability for any errors or omissions. Sitemate Power Systems reserves the right to modify specifications at any time.

P | 09 282 2366 E | sales@sitematepower.co.nz W | www.sitematepower.co.nz