

APPLICATIONS:

- The SM83 is a main distribution hub for Sitemate portable systems used throughout major construction projects
- Provides master isolation, sub circuit protection and sub board distribution.
- Compatible with SM17, SM16, SM7, SMTL10012 and SMTL20025

CONSTRUCTION:

- IP65 - suitable for outdoor use
- Aluminium powder coated enclosure
- Galvanised steel gear tray
- Built to AS/NZS 61439.4:2016
- Galvanised steel protective frame
- Solid rubber wheels
- Removable gland plate
- Lockable door
- Weight 111kgs including frame (Board 66kgs)
- Input Power - 250A, 400Va.c., 3PH + E + N, 50Hz.
- New Zealand designed and manufactured
- 1100mm(L) x 1680mm(H) x 700mm(D)

PRODUCT FEATURES:

- 2 Year Limited Warranty.
- Industry recognised switchboard components.
- Provision for additional Power Locks, IEC and AS/NZS Outlets.
- Provision for metering.
- Removable gland plate allows for a range of mains supply configurations.
- Well balanced and easy to manouvre frame.
- Compatible with all Sitemate equipment.
- Robust construction.
- Customisation available on request.



Code	Outlets	Quantity	Voltage	Configuration
SM83	63A	3	400 Va.c.	IEC, 3P + E + N
	32A	3	400 Va.c.	IEC, 3P + E + N
	16A	2	230 Va.c.	IEC, 2P + E (RCD Protected)
	15A	4	230 Va.c.	AS/NZS, 2P + E (RCD Protected)

Sitemate Power Systems has taken every precaution to ensure accurate information on this data page, but accept no liability for any errors or omissions. Sitemate Power Systems reserves the right to modify specifications at any time.