

sLED
by Switch Lighting

DOME



SLED315F
Ø100mm

Wide angle lighting




SLED215F | SLED715F
Ø84mm

Wide angle lighting


sLED DOME Fixed

SLED 215F | SLED315F | SLED715F

- + switchable CCT
- + CRI 90
- + pure convex diffusion
- + trim matches ZELA range
- + IP65 front



SLED315F



SLED715F
SLED215F

Beam control options

Beam angle



110°

Diffuser

Opaque

Other options

Trim colour



Textured white
RAL 9016



Textured black
B104

Pure colour options

Switchable CCT



2700K



3000K



4000K

CRI

Professional series (P) CRI 90

Driver

Phase cut dim (standard)

Product information

(example: 3000K, phase cut driver)

Model	Power (W)	Delivered lumens (lm)*	Insulation coverable		
			NZ	AU	UK/EU
SLED215F	7	690	ICF	IC4	✓
SLED715F	10	700	ICF	IC4	✓
SLED315F	10	800	ICF	IC4	✓

*Please note: lumens are for the white version. Lumens for the black are reduced.

SLED315F



Size
100x36mm



Cut-out
Ø86-89mm



Hole depth
>40mm



Front

SLED215F SLED715F



Size
84x37mm



Cut-out
Ø70-73mm



Hole depth
>40mm



Front

how to specify SLED Fixed

e.g. code = **SLED315F-W1S1P-TW**

Model	Beam	Switchable CCT	CRI	Trim Colour
SLED215F SLED715F SLED315F	W1 = 110° convex	S1 = 2700K 3000K 4000K	P = 90	TW = Textured white TB = Textured black

Please see www.switch-lighting.co.nz for full specifications, lux levels, SDoCs, ies files and installation instructions.



Warranty
5 Years

L70 (60,000 h)

