Product data sheet
Characteristics

XUZC50
Photoelectric sensors XU, accessory for sensor, reflector, 50 x 50 mm



Main

Range of product	Telemecanique Photoelectric sensors XU
Accessory / separate part category	Sensor accessories
Accessory / separate part type	Reflector
Accessory / separate part destination	Standard reflex photo-electric sensor
Shape of reflector	Square
Sale per indivisible quantity	1

Complementary

Accessory dimension	50 x 50 mm
Net weight	0.02 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	20 g
Package 1 Height	1.4 cm
Package 1 width	8.8 cm
Package 1 Length	7.6 cm
Unit Type of Package 2	BAG
Number of Units in Package 2	1
Package 2 Weight	20 g
Package 2 Height	1.4 cm
Package 2 width	8.8 cm
Package 2 Length	7.6 cm
Unit Type of Package 3	S02
Number of Units in Package 3	100
Package 3 Weight	2.174 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes


The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months

Dimensions


mm
in.
35
1.38
4xR5
51
2.01
69
2.72
47
1.85
60
2.36
4
0.16
8.1
0.32
2xØ4.5
2xØ0.18
2xØ5.5
2xØ0.22
51
2.01