



— PRODUCT DATA SHEET

W4R Work



— W4R Work

PRODUCT DESCRIPTION

Robust, versatile, compact: The Ledlenser W4R Work is a reliable work light for everyday workshop use. The superior Ledlenser light beam ensures precise and powerful illumination of work areas – either broadly via flood light or selectively via a spot LED in the lamp head. Thanks to the integrated magnet and swivelling base, the W4R Work can be flexibly positioned and aligned at any time. The powerful battery can be charged quickly and easily via USB-C and can be replaced if necessary. Other features include a clip for attaching to work clothing or equipment, a nubbed surface for a strong grip and a handy transport lock.

- Compact premium work light with two light sources for wide-area (flood) or spot illumination
- Robust plastic housing with non-slip surface structure
- Flexible mounting and illumination thanks to magnet and swivel mechanism
- Service-replaceable li-ion battery; easily rechargeable via USB-C, with battery and charge level indicator
- Transport lock prevents light from being accidentally turned on

TECHNICAL DATA

Width [mm]	28
Depth [mm]	20
Height [mm]	163
Weight incl. batteries [g]	91
Weight without batteries [g]	68
Focus function	No
Primary material	PC
Cartridge	No

POWER SUPPLY

Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion
Battery replaceable	No
Total battery voltage [V]	3.7
Total battery capacity [mAh]	760
Total battery energy ² [Wh]	2.812
Rechargeable	Yes
Charging time ⁵ [min]	120
Energy modes	Constant Light
Energy status indicator	Battery Indicator, Charge Indicator, Low Battery Warning

FURTHER SPECIFICATIONS

IP class	IP54
Drop test (drop height) [m]	1
IK Code [J]	7
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Low Power, Mid Power, Power

LIGHT SOURCE

	COB	Spot
Amount LEDs	1	1
LED type	COB LED	High Power LED
Color	White	White
Color temperature [K]	6000 to 7500	6000 to 7500
Color rendering index (CRI)	70	70

LIGHT VALUES - COB

ANSI – Constant Light	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]		220		60
Run time ¹ [h]		2		9

LIGHT VALUES - Spot

ANSI – Constant Light	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]			100	
Beam distance ¹ [m]			90	
Run time ¹ [h]			2	

SWITCH

Front Switch

FEATURES

Transportation lock , Flicker Free