

DA-250D

DUAL POWER AMPLIFIER

The DA-250D is a 2-Channel Digital Power Amplifier featuring lightweight, compact, high power output, and high efficiency. It delivers 250 W #x 2 channels (4 x# output) using a switching power supply. Each channel is equipped with an independent power section. It can be mounted in an EIA Standard equipment rack (1 unit size).



Article number:DA-250D CE301
Alternative products: DA-250FH


Specifications

Indicator	Power (blue) x 1, Input (green) x 2, Output (yellow) x 2, Peak (red) x 2, Protect (red) x 2
Power source	220 - 240 V AC, 50 / 60 Hz
Rated output	2 x 250 W (4 Ω) / 2 x 170 W (8 Ω)
Frequency response	20 Hz - 20 kHz (±1 dB)
Distortion (value)	< 0.1 %
Power source	220 - 240 V AC, 50 / 60 Hz
Rated output	2 x 250 W (4 Ω) / 2 x 170 W (8 Ω)
Distortion	< 0.1 % (at 1 kHz)
Power consumption	120 W (EN standard)
Frequency response	20 Hz - 20 kHz (±1 dB)
Power consumption	120 W (EN standard)
S/N ratio	100 dB (A-weighted)
Number of channels	2
Indicator	Power (blue) x 1, Input (green) x 2, Output (yellow) x 2, Peak (red) x 2, Protect (red) x 2
S/N ratio	100 dB (A-weighted)
Distortion	< 0.1 % (at 1 kHz)
Finish	Aluminium, Steel plate, alumite process, black,
Operating humidity	< 90% RH (no condensation)
Operating temperature	-10°C to +40°C

DA-250D



DUAL POWER AMPLIFIER

Appearance



Other product versions CE-GB and CE-AU are available depending on the power cord type.

Rear View

MODEL	AC plug
CE301	
CE-GB	
CE-AU	