

S-SERIES ENCLOSURES WEATHERPROOF IP66

FEATURES

- Transparent Door
- UV Stable ABS & Polycarbonate
- Lockable
- Suitable for PV Use
- Silicone Foam Seal
- Complies with AS/NZS 61439.1:201



Code	ZESWP4	ZESWP6	ZESWP9	ZESWP12
DIN Capacity	4 Pole	6 Pole	9 Pole	12 Pole
DIN Rail Fows	1 x 4 Way	1 x 6 Way	1 x 9 Way	1 x 12 Way
Neutral Links	1 x 4 Way	2 x 4 Way	2 x 6 Way	2 x 8 Way
Conduit Entries	• 4 x 25mm	• 4x 25mm • 2x 32mm	• 4x 25mm • 2x 32mm	• 6x 32mm • 4x 22mm
Dimensions (H x W x D)	• 197 x 130 x 100	• 197 x 164 x 100	• 197 x 220 x 100	• 226 x 272 x 108
Input Voltage	230V / 500V AC, 1000V DC			
Max Current Rating	110A			
Mounting	Surface			
Base Box Material	UV Stable & Flame Retardant ABS			
Door Material	Polycarbonate			
IP Protection	IP66			
Warranty	5 Years			
Compliance	AS/NZS 61439.1			
Rail	DIN - Galv Steel			

S-SERIES ENCLOSURES WEATHERPROOF IP66

FEATURES

- Transparent Door
- UV Stable ABS & Polycarbonate
- Lockable
- Suitable for PV Use
- Silicone Foam Seal
- Complies with AS/NZS 61439.1:201



Code	ZESWP18	ZESWP24	ZESWP36
DIN Capacity	18 Pole	24 Pole	36 Pole
DIN Rail Fows	1 x 18 Way	2 x 12 Way	2 x 18 Way
Neutral Links	2 x 14 Way	4 x 8 Way	4 x 14 Way
Conduit Entries	• 8x 32mm • 4x 22mm	• 6 x 32mm • 4 x 22mm	• 8 x 32mm • 4 x 22mm
Dimensions (H x W x D)	• 226 x 380 x 110	• 378 x 272 x 110	• 378 x 380 x 110
Input Voltage	230V / 500V AC, 1000V DC		
Max Current Rating	110A		
Mounting	Surface		
Base Box Material	UV Stable & Flame Retardant ABS		
Door Material	Polycarbonate		
IP Protection	IP66		
Warranty	5 Years		
Compliance	AS \ NZS 61439.5		
Rail	DIN - Galv Steel		