Product datasheet

Specifications

CLIPSAL

Night lamp, Iconic, with PIR motion sensor and switched socket cover frame, horizontal, extra black

3025NW-XB

Main

Range of product	Iconic
Range	Iconic
Product or component type	Cover frame
Aesthetic name	Iconic
Detection angle	40°
Movement detection area	2 m
Presence detection area	1 m
operating distance	2 m
Colour tint	Extra black (XB)
Number of rocker	1
Number of gangs	1 gang
Number of switched socket outlet	1

Complementary

Device mounting	Flush
fixing mode	Plug-in
Product destination	Switched socket
Main colour tint	Extra black
Surface finish	Matt
surface treatment	Untreated
Installation direction	Horizontal
Type of installation	Indoor
Height	78 mm
Width	120 mm
Depth	32 mm
Material	Thermoplastic
Net weight	64 g
Type of packing	Polybag
Quantity per set	Set of 1
Main material	Thermoplastic

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

IP degree of protection	IP20
Ambient air temperature for storage	-5…65 °C
Ambient air temperature for operation	0…45 °C
Relative humidity	10…85 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.2 cm
Package 1 Width	7.8 cm
Package 1 Length	12 cm
Package 1 Weight	64 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	32.8 cm
Package 2 Width	10.6 cm
Package 2 Length	14.6 cm
Package 2 Weight	763.645 g
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	33.5 cm
Package 3 Width	26.1 cm
Package 3 Length	33.5 cm
Package 3 Weight	4.166 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**60 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**22 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**38 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.1 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Recyclability potential, in %	**0**
End of life manual availability	**End of Life Information**
Removable battery	**No**

Image of product / Alternate images

Alternative

220V-240V~
50Hz

Product datasheet

3025NW-XB