LEDFIRE SM

Surface Mounted Emergency Luminaire



- Non-maintained operation with D63 classification
- Fully compliant (AS/NZS 2293)
- Weatherproof IP65 rating
- Low energy consumption (avg. 0.4W)
- Wall and ceiling mounting - rod mounting with rod mount kit
- High quality lithium battery (LiFePO4) and smart charger meets and exceeds relevant safety standards
- Smart charger protects and extends battery life and minimises power consumption
- Available in black or white
- Supports DALI-2 wired emergency testing
- Supports Ektor Lynk wireless emergency testing
- SafeTest - automated self-testing (AS2293/IEC62034)
- Includes easy-to-rewire junction box for DALI soft wiring leads

ORDERING INFORMATION

Order code	14859
Description	Ektor One Ledfire Surface Mount IP65 - D63 - W/Wireless and DALI
Driver Type	Lynk Wireless or DALI-2 with DT1
Item Code	EV-LEDFIRE-SM-ONE-IP65

MECHANICAL

IP Rating	IP65
Fitting Colour	White
Body Material	Polycarbonate
Installation Type	Surface mount

ELECTRICAL

Working Temp Range	0 to 40 °C
Input Frequency	50 Hz
Maximum Wattage	2 W
Input voltage	230Vac

In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%

Standby Power	0.4 W

Standby power for non-maintained/switched maintained emergency devices is measured when the light is off and the charger is in standby mode. For maintained emergency devices, standby power is measured when the light is on and the charger is in standby mode. Typically, charging occurs for the first 16 hours after the device is powered or after a battery discharge.

DRIVER

Driver Type	Lynk Wireless or DALI-2 with DT1
Wiring Type	Re-wireable terminal block (4 pin)

EMERGENCY (EM SUFFIX)

Emergency Mode	Non-Maintained
Emergency Classification	C0:D63, C90:D63
Emergency Output Power	2200 mW
Replacement Battery Code	18096
Emergency Duration	90 mins
Emergency Lumen Output	320 lm
Emergency Control	Lynk Wireless or DALI-2

COMPLIANCE

Standards	AS/NZS 60598.1 AS 60598.2.22 AS/NZS 61347.1 AS/NZS 61347.2.13 AS CISPR 15 AS/NZS 2293.3

© 2026 Evolt

WARRANTY

Warranty	8 Year Warranty, RTB


The total warranty period is shown above. Where an on-site period is listed, the first years are covered on-site, with return-to-base coverage for the remainder. For full warranty details and claim instructions, please refer to our Warranty page.

DIMENSIONS

Product Height	48 mm
Product Length	145 mm
Product Width	145 mm


LINE DRAWINGS

EV/LEDFIRE/SM/ONE/IP65



PHOTOMETRICS

EV/LEDFIRE/SM/ONE/IP65



Information is subject to change without prior notice. Images are for illustrative purposes only. E&OE