UMBRA CORE WIDE BODY DIFFUSED

Umbra Core WB Diffused Batten, Tri-Colour, Power

Switchable

- Tri-colour CCT selection (3000K/4000K/5700K)
- IP20 rated for indoor installation
- PMMA diffused optic for uniform light distribution
- Power switchable wattage (9W/13W/15W/18W)
- Exclusive 5 year warranty
- High lumen output up to 2,070lm at 4000K
- Surface mount installation



ORDERING INFORMATION

Order code	15544
Description	Umbra Core 600mm Tri-CCT Diffused Wide Body Batten - Fixed Output Driver
Driver Type	Fixed output
Item Code	EV-UMBRA-CORE-WB-DIFF-600

EFFICIENCIES

Total System Efficiency	124.8 lm/W

The performance of each component of a luminaire is demonstrated through its efficiencies, which together determine the total system efficiency of the product. The output of the LED chip is first multiplied by the optical and thermal efficiencies to calculate the Luminaire efficiency. However, this calculation does not consider the driver efficiency. To determine the overall efficiency of the system, the Luminaire efficiency must be multiplied by the driver efficiency, which accounts for all losses in the system.

MECHANICAL

IP Rating	IP20
Fitting Colour	White
Body Material	Powder-coated steel
Diffuser Material	PMMA
Installation Type	Surface mount

ELECTRICAL

Input Frequency	50 Hz
Power Factor	0.9
Maximum Wattage	18 W
System Max Wattage	18 W
Input voltage	220-240V~

LAMP

Colour Rendering Index (CRI)	>80
CCT Configuration	TRI-CCT
Beam Angle	125 °

LED LIFETIME

LED Lifetime	>54000 hrs

This is the Reported LED Lifetime in Hours based on TM-21. Ektor does not list the projected or calculated LED lifetime, which is normally longer as TM-21 Addendum B explicitly states "The Calculated and Projected Lp(Dk) are not to be reported". This Lifetime refers to the life of a single LED however the system life is longer since the probability and binomial distribution of all LEDs in the system means that the average led is performing above the specification and compensates for the LEDs falling below.


 © 2026 Evolt

COLOUR TEMPERATURE

9 Watts	
3000 K	1200 lm
4000 K	1240 lm
5700 K	1200 lm
18 Watts	
3000 K	2000 lm
4000 K	2070 lm
5700 K	1960 lm

LINE DRAWINGS

EV/UMBRA/CORE/WB/DIFF/600



DRIVER

Driver Type	Fixed output
Driver Included	Yes
Integrated Driver	No
Dimmable	No
Wiring Type	Re-wireable terminal block (3 pin)
Driver Mode	Constant Current

COMPLIANCE

Standards	AS/NZS 60598.1 AS/NZS 60598.2.1 AS/NZS 61347.1 AS/NZS 61347.2.13 AS CISPR 15

WARRANTY

Warranty	5 Year Warranty, RTB

The total warranty period is shown above. Where an on-site period is listed, the first years are covered on-site, with return-to-base coverage for the remainder. For full warranty details and claim instructions, please refer to our Warranty page.

DIMENSIONS

Product Height	74 mm
Product Length	620 mm
Product Width	124 mm

Information is subject to change without prior notice. Images are for illustrative purposes only. E&OE