



M40 Type 8 with
Trimless Frame

M40-T8 Type 8 - Adjustable Scopic

Watts 4W / 350mA **Lumens** 170lm

Beam 36° **Tilt** 30° **Rotate** 360°

Specifications

CCT	2700K, 3000K or 4000K
Binning	SDCM 3
Lifespan	105,000hrs (L90 B10)
UGR	Suitable for installations requiring UGR of less than 19.

Material	Aluminium
CRI	97
IP Rating	IP43
Classification	IC Rated
Driver	Sold separately
Warranty	5 Year Warranty

White


Black

Dimensions



M40-T8

Step 1: Choose Installation Frame

See pages 130-131 for frame details







	Recessed Round	Recessed Oval Double	Recessed Square	Recessed Rectangular Double	Trimless
Dimensions	Ø63 x H50mm	L116 x W63 x H50mm	L63 x W63 x H50mm	L116 x W63 x H50mm	Ø105 x H52mm
Cut Out	Ø57mm	2x Ø57mm @53mm centres	Ø57mm	2x Ø57mm @53mm centres	Ø85mm
White Code	F40-RR-W	F40-RR2-W	F40-RSQ-W	F40-RSQ2-W	F40-TL-R
Black Code	F40-RR-B	F40-RR2-B	F40-RSQ-B	F40-RSQ2-B	

Step 2: Choose Module Type

Model	- Type	- Trim/Body Colour	Reflector Colour	CCT	- Beam
M40	- T8	- W (White), B (Black)	B (Black)	27K (2700K) or 3K (3000K), (4000K indent only)	- 36D

Step 3: Select your Driver

	Phase-cut Dimmable	Dali	Casambi
M40-T8	DCC200350-DMS-4W8W @ 350mA	DCC150700-DDM-612W @ 350mA	DCC150500-CAS-712W @ 350mA (does not fit through cutout, ceiling access required)

Configuration Example: For a Recessed Single M40-T8 Adjustable Spot in White and a Phase-cut Dimmable Driver, the following three components must be ordered. (1) Recessed Frame: F40-RR-W (2) Light Module: M40-T8-WB3K-36D (3) Dimmable Driver: DCC200350-DMS-4W8W.



F40-RR Recessed Round

Dimensions Ø63 x H50mm
Cut Out Ø57mm
White Code F40-RR-W
Black Code F40-RR-B



F40-RR2 Recessed Oval Double

Dimensions L116 x W63 x H50mm
Cut Out 2x Ø57mm @ 53mm centres
White Code F40-RR2-W
Black Code F40-RR2-B



F40-RSQ Recessed Square

Dimensions L63 x W63 x H50mm
Cut Out Ø57mm
White Code F40-RSQ-W
Black Code F40-RSQ-B



F40-RSQ2 Recessed Rectangular Double

Dimensions L116 x W63 x H50mm
Cut Out 2x Ø57mm @ 53mm centres
White Code F40-RSQ2-W
Black Code F40-RSQ2-B



SF40-RR Surface

Dimensions L170 x W60 x H60mm

White Code SF40-RR-W

Black Code SF40-RR-B

SF40 not compatible with M40-T2/T3/T9/T10



F40-TL-R Trimless

Dimensions Ø105 x H52mm

Cut Out Ø85mm

Code F40-TL-R