



M60 Type 8 with
Trimless Frame

M60-T8 Type 8 - Adjustable Scopic

Watts 7W / 200mA DC **Lumens** <700lm

Beam 24˚, 36˚ or 55˚ **Tilt** 40˚ **Rotate** 355˚

Specifications

CCT	3000K or 4000K
Binning	SDCM 2
Lifespan	105,000hrs (L90 B10)
UGR	Suitable for installations requiring UGR of less than 19.

Material	Aluminium
CRI	97
IP Rating	IP43
Classification	IC Rated
Driver	Sold separately
Warranty	5 Year Warranty

White


Black

Dimensions



M60-T8

Step 1: Choose Installation Frame

See pages 168-169 for frame details








	Recessed Round	Recessed Oval Double	Recessed Square	Recessed Rectangular Double	Trimless	Surface Cylinder
Dimensions	Ø81 x H60mm	L153 x W81 x H60mm	L81 x W81 x H60mm	L153 x W81 x H60mm	Ø130 x H58mm	Ø85 x H130mm**
Cut Out	Ø75mm	2x 75mm @ 72mm centres	Ø75mm	2x 75mm @ 72mm centres	Ø105mm	-
White Code	F60-RR-W	F60-RR2-W	F60-RSQ-W	F60-RSQ2-W	F60-TL-R	SF60-RR-W
Black Code	F60-RR-B	F60-RR2-B	F60-RSQ-B	F60-RSQ2-B		SF60-RR-B

**Remote driver only, driver cannot be installed inside surface frame.

Step 2: Choose Module Type

Model	- Type	- Trim/Body Colour	Reflector Colour	CCT	- Beam
M60	- T8	- W (White), B (Black)	B (Black)	27K (2700K) or 3K (3000K), (4000K indent only)	- 24D, 36D or 55D

Step 3: Select your Driver

	Phase-cut Dimmable	Dali	Casambi
M60-T8	DCC120200-DMS-5W8W-STR @ 200mA	DCC150700-DDM-612W @ 200mA	DCC150500-CAS-712W @ 180mA

Configuration Example: For a Trimless Single M60-T8 Adjustable Spot in White and a Phase-cut Dimmable Driver, the following three components must be ordered. (1) Trimless Frame: F60-TL-R (2) Light Module: M60-T8-WB3K-36D (3) Dimmable Driver: DCC120200-DMS-5W8W-STR.



F60-RR Recessed Round

Dimensions Ø81 x H60mm
Cut Out Ø75mm
White Code F60-RR-W
Black Code F60-RR-B



F60-RR2 Recessed Oval Double

Dimensions L153 x W81 x H60mm
Cut Out 2x 75mm @ 72mm centres
White Code F60-RR2-W
Black Code F60-RR2-B



F60-RSQ Recessed Square

Dimensions L81 x W81 x H60mm
Cut Out Ø75mm
White Code F60-RSQ-W
Black Code F60-RSQ-B



F60-RSQ2 Recessed Rectangular Double

Dimensions L153 x W81 x H60mm
Cut Out 2x 75mm @ 72mm centres
White Code F60-RSQ2-W
Black Code F60-RSQ2-B



SF60-RR Surface Cylinder

Dimensions Ø85xH130mm

White Code SF60-RR-W

Black Code SF60-RR-B



F60-TL-R Trimless

Dimensions Ø130xH58mm

Cut Out Ø105mm

Code F60-TL-R