# High Performance Tape 19mm x 0.18mm Black 20m

## Application

Implementation of cable harnesses, splicing, wire and cable terminations.
Repairing conduits.
Electrical insulation at high and low temperatures.
Suitable for outdoor use, UV-resistant.



## Design Specifications

- Material: Vinyl Electrical Tape, Rubber Adhesive
- Dimensions: 19mm x 20m x 0.18mm.
- Tensile strength: 32N/cm.
- Elongation at break: 240 %.
- Adhesion to steel 2B: 2.25N/cm.
- Adhesion to backing: 2.15N/cm.
- Dielectric strength: 40kV/mm.
- Insulation resistance: 5.0 x 109Ω/25mm.
- Operating temperature: -18°C to +105°C.
- Application temperature: -10°C to +40°C.
- Application method: Recommended 50% overlap.
- Standards: EN 60454, IEC 60454-3-1-2002
- Colour: Black




## Compliance

40046958

Comply With Standard EN60454-3-1 -2002

FLAME RETARDANT

RoHS COMPLIANT

## General Information

| Part No. | Colour | Length (m) | Width (mm) | Thickness (mm) | QTY | Packaging Type |
|---|---|---|---|---|---|---|
| HAMHPT1920BK | Black | 20 | 19 | 0.18 | 1 | Box |

## Logistic Information

**Individual Packaging**

x1

**Plastic Box**
Heigth (cm): 2.3
Width (cm): 9.6
Depth (cm): 9.6
Net Weigth (kg): 0.09
Gross Weight (kg): 0.11

**Outer Box Packaging**

x100

**Carton Box**
Heigth (cm): 40
Width (cm): 35
Depth (cm): 28
Net Weigth (kg): 11
Gross Weight (kg): 11.6