Multifunctional electrical installation tester
MI 3136 InstalTest COMBO XC

Parkway Process Solutions

Multifunctional electrical installation tester



Low-voltage electrical safety is one of the most important considerations when protecting domestic and office users. For anyone committed to ensuring reliable, compliant, and user-friendly safety testing, the MI 3136 **InstalTest** COMBO XC is an exceptional choice. Its compact, portable design makes it suitable for a wide range of applications. The instrument delivers fast, accurate results while helping technicians maintain the highest electrical safety standards.

KEY FEATURES

- PASS/FAIL limits to AS/NZS 3017;
- Replaces 5 instruments with 12 tests in one instrument;
- Verification, fault-finding and diagnosis of live and dead installations, and compliance testing to AS/NZS 3017;
- Auto-sequences to verify sockets and installations in seconds by combining up to 6 single tests into a single push button sequence;
- High volume RCD testing procedure;
- 5 instruments-in-one with reporting:
  - Multimeter;
  - Insulation Tester;
  - RCD Tester;
  - Loop Impedance & Phase Sequence Tester
- Save test results and download PDF test reports for customers and record keeping;
- Built-in help screens for referencing on site;
- Built-in fuse tables for automatic evaluation of the line / loop impedance result;
- Monitoring of all 3 voltages in real-time;
- Automatic polarity reversal on continuity test;
- Measurement filtering according to the selected area group;
- **Wi-Fi** and **Bluetooth®** connectivity for **fast communication** with Metrel Cloud for measurement planning, data management and reporting. *
- Metrel Cloud Storage compatible.
- Metrel Cloud App compatible.
- PC SW Metrel ES Manager: Enables creation of test structures, professional test reports and data transfer for archiving. *

** Available with MESM PRO and Metrel Cloud licences.*

TECHNICAL SPECIFICATION

Main function	Sub-function	Measuring range	Resolution	Accuracy
CONTINUITY	Test current 7 mA 2-wire	0.0 Ω ... 19.99 Ω	0.1 Ω	±(5 % of reading + 3 digits)
		20 Ω ... 1999 Ω	1 Ω	±(5 % of reading + 3 digits)
	Test current 200 mA 2-wire	0.00 Ω ... 19.99 Ω	0.01 Ω	±(3 % of reading + 3 digits)
		20.0 Ω ... 199.9 Ω	0.1 Ω	±(5 % of reading)
		200.0 Ω ... 1999 Ω	1 Ω	±(5 % of reading)
	Rpe (RCD: No)	0.00 Ω ... 19.99 Ω	0.01 Ω	±(5 % of reading + 5 digits)
		20.0 Ω ... 199.9 Ω	0.1 Ω	±(5 % of reading + 5 digits)
		200 Ω ... 1999 Ω	1 Ω	±(5 % of reading + 5 digits)
	Rpe (RCD: Yes, no trip out)	0.00 Ω ... 19.99 Ω	0.01 Ω	±(5 % of reading + 10 digits)
		20.0 Ω ... 99.9 Ω	0.1 Ω	±(5 % of reading + 10 digits)
		100 Ω ... 199.9 Ω	0.1 Ω	±10 % of reading
		200 Ω ... 1999 Ω	1 Ω	±10 % of reading
INSULATION RESISTANCE	R iso test voltage 50/100/250 V	0.00 MΩ ... 19.99 MΩ	0.01 MΩ	±(5 % of reading + 3 digits)
		20.0 MΩ ... 99.9 M Ω	0.1 MΩ	±(10 % of reading)
		100.0 MΩ ... 199.9 MΩ	0.1 MΩ	±(20 % of reading)
	R iso test voltage 500 V	0.00 MΩ ... 19.99 MΩ	0.01 MΩ	±(5 % of reading + 3 digits)
		20.0 MΩ ... 199.9 MΩ	0.1 MΩ	±(5 % of reading)
		200 MΩ ... 999 MΩ	1 MΩ	±(10 % of reading)
	R iso test voltage 1000 V	0.00 MΩ ... 19.99 MΩ	0.01 MΩ	±(5 % of reading + 3 digits)
		20.0 MΩ ... 199.9 MΩ	0.1 MΩ	±(5 % of reading)
		200 MΩ ... 999 MΩ	1 MΩ	Indicative
	Um	0 V ... 1200 V	1 V	±(3 % of reading + 3 digits)
RCD	RCD Uc	0.0 V ... 19.9 V	0.1 V	(-0 %/+15 %) of reading ± 10 digits
		20.0 V ... 99.9 V	0.1 V	(-0 %/+15 %) of reading
	RCD RL	0 ... 9999 Ω	1 Ω	Calculated value (RL=U/IΔN)
	RCD (t)	0.0 ms ... 40.0 ms	0.1 ms	±1 ms
		40.1 ms ... 999.9 ms	0.1 ms	±3 ms
		1000 ms ... 1999 ms	1 ms	±3 ms
		2.00 s ... 10.00 s	10 ms	±3 ms
	RCD I Ramp	0.1 m... 99.9 mA 0.1 mA ± 10 %		±0.1´ID
		100 m ... 999 mA 1 mA ± 10 %		±0.1´ID
		1.00 ... 1.10 A 10 mA ± 10 %		±0.1´ID
IMPEDANCE	Zline (L-L, L-N), Zloop (L-PE)	0.00 Ω ... 9.99 Ω	0.01 Ω	±(3 % of reading + 3 digits)
		10.0 Ω ... 99.9 Ω	0.1 Ω	±(3 % of reading + 3 digits)
		100 Ω ... 999 Ω	1 Ω	±(10 % of reading)
		1.00 kΩ ... 9.99 kΩ	10 Ω	±(10 % of reading)
	Zs RCD	0.00 Ω ... 9.99 Ω	0,01 Ω	±(5 % of reading + 10 digits)
		10.0 Ω ... 99.9 Ω	0,1 Ω	±(5 % of reading + 10 digits)
		100 Ω ... 999 Ω	1 Ω	±(10 % of reading)
		1.00 kΩ ... 9.99 kΩ	10 Ω	±(10 % of reading)
	Uc	0.0 % ... 99.9 %	0.1 %	Consider accuracy of Zline measurement(s)
VOLTAGE	Voltage	0 V ... 550 V	1 V	±(2 % of reading + 2 digits)
	Frequency	14.0 Hz ... 499.9 Hz	0.1 Hz	±(0.2 % of reading + 1 digit)
EARTH RESISTANCE	3-wire	0.00 Ω ... 19.99 Ω	0.01 Ω	±(5 % of reading + 5 digits)
		20.0 Ω ... 199.9 Ω	0.1 Ω	±(5 % of reading + 5 digits)
		200.0 Ω ... 9999 Ω	1 Ω	±(5 % of reading + 5 digits)
GENERAL	Power supply	7,2 V (5200 mAh) Li-ion battery pack		
	Measuring category	600 V CAT III; 300 V CAT IV		
	Protection class	Double insulation		
	COM port	Bluetooth, USB Type-C		
	Display	Colour TFT display, 4.3 inch, 480 x 272 pixels		
	Weight	1.78 kg		
	Size (l x h x w)	252 x 111 x 165 mm		

USED FOR

- Initial and periodic testing and inspections of domestic and small-office low-voltage installations;
- Testing of TT and TN systems;
- Fire safety and hazards testing;
- Installation troubleshooting;
- Electric vehicle supply equipment (EVSE) testing;
- Maintenance (Preventive, Predictive, Corrective, Reactive repairs);
- Low-voltage earthing and lightning protection.

USED BY

- Students, entry level and small electricians;
- Office-based businesses;
- Technical aid organizations (fire brigades, ministry of defence, healthcare, etc.);
- Public sector;
- Hotels and restaurants;
- Construction businesses;
- Facility maintenance personnel;
- Rental companies;
- Small to medium electrical installation companies;
- Entry level electrical inspectors.

STANDARDS

Functionality
- IEC/EN 61557

Electromagnetic compatibility (EMC)
- EN 61326-1
- EN 61326 - 2-2

Safety (LVD)
- EN 61010-1
- EN 61010-2-030
- EN 61010-031
- EN 61010-2-032

Reference standards for electrical installations and components
- AS/NZS 3017
- EN 61009
- IEC 60364-4-41
- BS 7671
- IEC 62752
- IEC 62955



OPTIONAL ACCESSORIES

Photo	Order No.	Acc. description
	A 1401	Remote Probe
	A 1298	Test probe, Brown
	A 1015	Test probe, Blue
	A 1062	Test probe, Green
	A 1297	Crocodile clip, Brown
	A 1310	Crocodile clip, Blue
	A 1309	Crocodile clip, Green
	A 1296	Test cable, BRN/GRN/BLU, 1.5m, 0.75mm2
	A 1053	Test cable, 1.5m, 0.75mm2
	A 1857	USB cable, Type C

Photo	Order No.	Acc. description
	A 1289	Soft padded carrying bag Size: M
	A 1191	Receiver 10k
	S 2027	3-wire Earth measurement set, 50m
	S 2058	Isolation resistance measurement set
	A 1012	Test lead, Green, 4m, 0.75mm2
	A 1154	Test lead, Black, 4m, 0.75mm2
	A 1153	Test lead, Black, 20m, 0.75mm2, Reel
	A 1164	Test lead, Black, 50m, 0.75mm2, Reel
	A 1778	Test probe, Black - Magnet tip
	A 1854	Telescopic probe CAT IV 1000V, Lmax = 2.1m

ORDERING INFORMATION



MI 3136 Standard Set

- Instrument MI 3136 InstalTest COMBO XC
- 1x A 1298 Test probe, Brown
- 1x A 1015 Test probe, Blue
- 1x A 1062 Test probe, Green
- 1x A 1297 Crocodile clip, Brown
- 1x A 1310 Crocodile clip, Blue
- 1x A 1309 Crocodile clip, Green
- 1x A 1296 Test cable, BRN/GRN/BLU, 1.5m, 0.75mm2
- 1x A 1053 Test cable, 1.5m, 0.75mm2
- 1x A 1857 USB cable, Type C
- Calibration certificate
- Short instruction manual
- Instruction manual*
- Metrel ES Manager BASIC Licence*
- SW 1201 Metrel ES Manager

MI 3136 Advanced Set

- MI 3136 Standard Set, also including:
- 1x A 1551 Large Padded Carrying Bag
- 1x A 1401 Remote Probe
- 1x A 1195 Resistor Box
- 1x A 1012 Trailing Lead - 4M Green
- 1 x MD-106 Non-Contact Voltage Detector

**SW 1201 Metrel ES Manager and all documentation can be downloaded free of charge from Metrel Web server (https://www.metrel.si/en/downloads/) or Metrel Documentation center (https://doc.metrel.si).*

SOFTWARE

Photo	Order No.	Acc. description
	SW 1201	Metrel Electrical Safety Manager (MESM)
	SW 1404	Metrel Cloud Storage
	SW 1406	Metrel Cloud App

CAN BE USED TOGETHER WITH

Photo	Order No.	Acc. description
	A 1532 XA	EVSE Adapter XA

Parkway Process Solutions

A leading provider of innovative water treatment

PRODUCTS | SERVICES | SOLUTIONS | TECHNOLOGY

PPS - MELBOURNE (Head Office)
Unit 4 & 5, 45 Bunnett St
Sunshine North, VIC, 3020
+61 (0) 3 9069 3200

PPS - PERTH (WA Operations)
52-54 Irvine St
Bayswater, WA, 6053
+61 (0) 8 9249 9003

PPS - DARWIN (Mawpump)
8 Toupein Rd
Yarrawonga, NT, 0830
+61 (0) 8 8931 2511

TANKWELD GROUP (Engineering & Installations)
75 Boundary Rd
Carrum Downs, VIC, 3201
+61 (0) 3 9775 1376