GTR501/2/3 ARCO

THREE CIRCUIT TRACK SPOT LIGHT



FEATURES

- Die-cast aluminium body
- Powder coated finish in white or black
- Anodised aluminium reflector 140-170lm/W
- Constant current LED driver included
- Colour matching 3 MacAdam steps
- LED lifespan: 50000 hours @ L80 B10, Ta 25°C
- Ta: -20°C to + 40°C

IMAGES




Selectable wattage via DIP switch



CCT selectable via DIP switch

DIMENSIONS



MODEL NO.	D	L1	W	L2
GTR501	Φ64	147	158	87
GTR502	Φ83	174	158	115
GTR503	Φ92	200	158	140

Unit: mm

TECHNICAL SPECIFICATIONS

MODEL NO.	INPUT VOLTAGE (V)	POWER (W)	OUTPUT CURRENT (mA)	LUMEN (lm)	COLOUR TEMPERATURE (K)	CRI	R9	BEAM ANGLE (°)	FITTING COLOUR	CARTON QUANTITY
GTR501 TC WH	230	10/12/ 14/15	250/300/ 350/400	1050/1240/ 1420/2060	3000/4000/5700	>90	>74	45	White	18
GTR501 TC BK									Black	
GTR502 TC WH		18/20/ 22/25	450/500/ 550/600	2900/3350/ 3550/3800				36	White	12
GTR502 TC BK									Black	
GTR503 TC WH		32/34/ 36/38	850/900/ 950/1000	3900/4000/ 4200/4450				45	White	6
GTR503 TC BK									Black	

Specifications above are for reference only and may vary without prior notice