Nipper LED Batten

NIPBAT202ECS

- Designed with a wide 130mm width base to easily replace old and energy consuming twin fluorescent battens.
- Flicker free LED driver built-in for increased visual acuity and comfort
- Option for emergency with Lithium Iron Phosphate Battery 2.5w @ 350lumen available

COLOUR SELECT

Performance

System Power	18W
Exit Lumen	1700lm, 1900lm, 1700lm
Lm/W	94lm/W, 105lm/W, 94lm/W
CCT	4000K, 5000K, 6500K
CRI	80
Operating Temperature	0 - 40°C
MacAdam Steps	5SDCM
Ingress Protection Rating	IP20
Beam Angle	120°
Lifetime	54,000hrs (L80/50)


Physical

Dimensions	L630 x W130 x H74mm
Diffuser	Polycarbonate
Luminaire Colour	White
Weight	1kg
Luminaire Material	Steel (Mild)
Driver Location	Integrated
Finish	Powder Coated
Installation	Surface Mounting

Electrical

Dimming	Non - Dimmable
Voltage	240V
Line Voltage Frequency	50Hz/60Hz
Inrush Current	12A
Inrush Current Duration	350µs
Line Current	0.07A
Electrical Rating	Class 1

Line Drawings



Product Images

*Rated LED design life where stated is based upon application of Pierlite's operating and maintenance guidelines; see pierlite.com.au. Actual product life may vary dependent upon frequency of maintenance and product application. Due to continual product improvement, information is subject to change without notification. Gerard Lighting Pty Ltd standard Terms and Conditions apply

PM 9:11:38 2/18/2021

Pierlite is a registered trademark of
Gerard Lighting Pty Ltd @Copyright Pierlite 2020

www.pierlite.com.au