PIERLITE® LED

SURFACE MOUNT | IP65 | IK08

COLOUR SELECT



POLO BULKHEAD GEN2

PRODUCT DETAILS


Size: Ø350mm, Ø430mm
Rated life: L70 B50 54000hrs
LED: Colour Select 3000K/4000K/5700K, CRI80, 6SDCM
Beam angle: Symmetrical, 120°
Driver: Integral, Non dimmable
Flicker free: PstLM≤0.022, SVM≤0.038
Rating: IP65, IK08, Class II
Operating temperature: -20°C to +40°C
Housing: Polycarbonate (PC)
Finishing: White
Diffuser/Lens: Polycarbonate (PC), Frosted
Connection: PG9/Ø16mm cable gland, Back entry/Side entry
Warranty*: 5 year


MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)


Dimming, Emergency (compliant to AS/NZS 2293), Sensor

APPLICATIONS

Surface mounted (ceiling/wall), Internal/External
Commercial, Industrial, Residential, Apartments







CODE	DESCRIPTION	POWER	LUMENS	EFFICACY	WEIGHT
POLO2-14W	POLO BULKHEAD 350 14W 3/4/57K @ 3K	14W	1300LM	93LM/W	1.50KG
POLO2-21W	POLO BULKHEAD 430 22W 3/4/57K @ 3K	22W	2100LM	95LM/W	2.00KG

*Please refer to the warranty policy at www.pierlite.co.nz; "POWER" is tested system powers from luminaire; "LUMENS" is delivered lumens from luminaire, including thermal, electrical and optic losses; ^Figures are interpolated / extrapolated from data at other versions.