Weatherlux Exit Light Gen2

The Weatherlux DALI is a versatile, IP65 exit luminaire suitable for damp environments and areas such as warehouses, production facilities, car parks and schools



- Durable white IP65 polycarbonate body, available for ceiling or wall mounting
- Save time and money while ensuring accuracy with integrated NFC functionality, allowing short addresses to be assigned without powering the exit light
- Automatic self-test with health status when not connected to DALI2/ Interact

IP65	IK08	0 to 50	50,000hrs (L70/B50)	4 Years
Ingress Protection Rating	Impact Rating	Operating Temperature	Lifetime	Warranty

CODE	SYSTEM POWER	DIMENSIONS	WEIGHT
WLUX-CM	5W	L350 x W110 x H80 mm	2.3kg
WLUX-CMIA	5W	L350 x W110 x H80 mm	2.3kg
WLUX-WM	5W	L350 x W110 x H80 mm	1.2kg
WLUX-WMIA	5W	L350 x W110 x H80 mm	1.2kg

CLASSIFICATION	EMERGENCY MODE WATTAGE	OPTION	BATTERY	BATTERY CHARGE	BATTERY VOLTAGE	BATTERY CAPACITY
CO/C180 D10 C90/C270:D10	2.2W	Maintained	LiFePO4	4hr	3.2V	3200mA

ACCESSORY CODE	DESCRIPTION
DGLCEM3200/1L11	Battery LiFePO4 1 Cell 3.2V 3200mAh

AS/NZS 2293.1:2018 Classification Table

Ceiling Mount

Allowable Luminaire Mounting Height (m)	Luminaire Maximum Spacing for each plane (m)		
	C0	C90 C270	C180
2.1	10.2	10.2	10.2
2.4	10.5	10.5	10.5
2.7	10.8	10.8	10.8


WLUX-CM

Wall Mount


Allowable Luminaire Mounting Height (m)	Luminaire Maximum Spacing for each plane (m)		
	C0	C90 C270	C180
2.1	9.4	10.2	
2.4	9.7	10.5	
2.7	9.9	10.8	

WLUX-WM

Line Drawings



WLUX-CM, WLUX-CMIA



WLUX-WM, WLUX-WMIA

Product Images



WLUX-WM, WLUX-WMIA

*Rated LED design life where stated is based upon application of Pierlite's operating and maintenance guidelines; see pierlite.com.au. Actual product life may vary dependent upon frequency of maintenance and product application. Due to continual product improvement, information is subject to change without notification. Gerard Lighting Pty Ltd standard Terms and Conditions apply

PM 8:38:34 2026-11-02

Pierlite is a registered trademark of
Gerard Lighting Pty Ltd @Copyright Pierlite 2020